



## AIR DRIVEN SAW

### Dimensions

Length(mm).....: 400                      Width(mm).....: 41                      Height(mm).....: 135  
Equipment Weight - (kg).....: 11  
Lifting/ Transportation.....: Transportation on pallet

### Area of use / certification

Onshore/offshore.....: Offshore  
Standard.....: Atex, IM2ExhIMbT5

### Type

Description.....: Air driven saw - Chain/clamp mounted  
Fabricator.....: Spitznas  
Model.....: Reciprocating Saw  
Serial no.....: 11639

### Flow / Pressure / Volume

Speed (stroke/min).....: 330  
Stroke length (mm).....: 60

### Connections

Air connection.....: Please specify with order (Claw, hansen, osv)  
Air supply (P@Q).....: 5-6 bar (max 6 bar)  
Air consumption : 1,45 m3/min

### Additional information

Equipment / Functions.....: Must be used with water-separator and oil-lubricator.

Blade must be ordered separately.

Blades:

FOFEIFEIN300 Sawblade 300x28x1.5 - 16z  
FOFEIFEIN400 Sawblade 400x28x1.5 - 16z  
FOFEIFEIN401 Sawblade 400x25x1.5 - 8z  
FOFEIFEIN402 Sawblade 400x25x1.7 - 6z  
FOFEIFEIN500 Sawblade 500x28x2.0 - 6z 724 0140  
FOFEIFEIN501 Sawblade 500x28x2.0 - 16z 724 1060  
FOFEIFEIN600 Sawblade 600x28x2.0 - 14z  
FOFEIFEIN601 Sawblade 600x28x2.0 - 8z