



DIAPHRAGM PUMP

Dimensions

Length(mm).....: 650 Width(mm).....: 500 Height(mm).....: 910
 Weight (kg).....: 74
 Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet

Construction year

Built.....: 2018
 Upgraded/rebuilt.....: 2023

Area of use / certification

Onshore/offshore.....: Offshore
 Standard.....: EX/Atex, CE, Norsok, Zone 1

Type

Fabricator.....: RAASM
 Model.....: AABM-2-N
 Serial no.....: 053000009-2023 (Art no. 3C6/5066VNHH)

Flow / Pressure / Volume

Q-max (l/min).....: 580
 P-max (bar).....: 8 P-max (PSI).....: 115
 Max temp. (GrC).....: 82

Connections

Inlet connection.....: 2" Camlock Male
 Outlet connection.....: 2" Camlock Female
 Air connection.....: 1" offshore claw coupling
 Air supply (P@Q).....: Max 6,7 bar

Additional information

Equipment / Functions.....: Pressure regulator on airsupply to regulate flow / pressure.
 Pump material Aluminium
 Nitril membrane/valve kit

Max feed pressure fluid side: 4-5bar (must be lower than air supply).
 Max particle size: 6,5mm
 Suction height dry / wet: 5/7,5m