



DIAPHRAGM PUMP

Dimensions

Length(mm).....:	650	Width(mm).....:	500	Height(mm).....:	830
Weight (kg).....:	73				
Lifting/ Transportation.....:	Mounted in Frame. Transportation on pallet				

Area of use / certification

Onshore/offshore.....:	Offshore
Standard.....:	EX/Atex, CE, Norsok, Zone 1

Type

Fabricator.....:	RAASM
Model.....:	AAB-2-N-580
Serial no.....:	052100003-2018 (Art no. 3C6/50111 NHH)

Technical information

Q-max (l/min).....:	580		
P-max (bar).....:	8	P-max (PSI).....:	115
Flowrate1.....:	500 ltr/min @ 1 bar		
Flowrate2.....:	320 ltr/min @ 4 bar		
Flowrate3.....:	100 ltr/min @ 7 bar		
Max temp. (GrC).....:	100		

Connections

Inlet connection.....:	2" Camlock Male
Outlet connection.....:	2" Camlock Female
Air connection.....:	1" offshore claw coupling
Air supply (P@Q).....:	Max 6,7 bar

Additional information

Equipment / Functions.....:	Max suction, dry : 5,0 metres
	Pressure regulator on airsupply to regulate flow / pressure.
	Pump material 316SS