



DIAPHRAGM PUMP

Dimensions

Length(mm).....: 510
 Weight (kg).....: 17
 Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet
 Width(mm).....: 350
 Height(mm).....: 510

Area of use / certification

Onshore/offshore.....: Offshore
 Standard.....: EX/Atex, CE, Norsok, Zone 1

Type

Fabricator.....: RAASM
 Model.....: ABB-12-N-60
 Serial no.....: 021300052-2018 (Art no. 3C1/26111 NHH)

Flow / Pressure / Volume

Q-max (l/min).....: 70
 P-max (bar).....: 8
 Max temp. (GrC).....: 100
 P-max (PSI).....: 115

Connections

Inlet connection.....: 1" Camlock Male
 Outlet connection.....: 1" Camlock Female
 Air connection.....: 1" offshore claw coupling
 Air supply (P@Q).....: Max 6,7 bar

Additional information

Equipment / Functions.....: Pressure regulator on air supply for flow / pressure control.
 Ground cable with clamp and documentation tube.
 Aluminum pump housing.

Max feed pressure fluid side: 4-5bar (must be lower than air supply).
 Max particle size: 1,5mm
 Suction height dry / wet: 4,5/7,5m