Unit no. PBM-018

IKM Testing AS

BEVEL MACHINE

Dimensions

Length(mm).....: 840 Width(mm).....: 610 Height(mm).....: 325
Weight - (kg).....: 34
Lifting/ Transportation.....: 1 ea plastic-case. Transportation on pallet

Area of use / certification

Onshore/offshore.....: Offshore

Type

Description.....: Bevel Machine - Bevelmaster
Fabricator.....: Tri Tool
Model.....: 206B
Serial no.....: 594239
Mounting (ID / OD).....: Internal (ID)

Flow / Pressure / Volume

Range of use - Minimum (Ø mm)....: 87.4
Range of use - Max recom.(Ø mm).: 609.6

Connections

Air connection.....: Hansen coupling
Air supply (P@Q).....: 1 m³/min @ 6,3 bar.

Additional information

Equipment / Functions.....: When used with pneumatic feed - to be used with water seperator/lubricator.

Absolute maxsimum OD : 24" (609.6mm) when connected with single point unit (extras).
Can be supplied with Full Support Pad, Flange Facer and Single Point Unit.

Portable ID mount machine tool for bevelling, facing and counterboring the ends of pipe or tubing in preparation for welding, can be used in EX – Zone.
Low weight, easy to assembly. Adjustable ID system