



HIGH PRESSURE TEST PLUG - ELBOW

Dimensions

Equipment Weight - (kg).....: 6
 Lifting/ Transportation.....: Transportation on pallet

Construction year

Built.....: 2019

Type

Item type.....: Testplug for Elbow / Bend
 Fabricator.....: Curtiss Wright
 Model.....: GTLBO-4P40

Flow / Pressure / Volume

P-max (bar).....: 231 P-max (PSI).....: 3350
 Nominal Pipe Size (Inches).....: 4.00
 Nominal Pipe Schedule.....: 40 / STD
 Plug Outside Ø (mm).....: 98.8
 Range of use - Minimum (Ø mm).....: 101.6
 Range of use - Max recom.(Ø mm): 104.4
 Plug Length (mm).....: 214

Additional information

Equipment / Functions.....: Installation:
 Normal Installation Torque : 204 Nm
 Maximum Installation Torque : 407 Nm

Eliminate welding on end caps/pups with GripTight Elbow Plug. Designed for testing piping, spools and pipe systems terminating in long radius elbows.

Features

- Orientation Free Installation - no need to align with elbow
- Patented Dual-Serrated GripTight MAX® gripper design
- Patented Floating, Self-Aligning grippers & seal
- Easy Installation - No welding or hot work required
- Ideal for horizontal & vertical applications
- Fits any long radius elbows
- Self-gripping design uses test pressure to increase holding power
- Saves significant time vs. welded-on end cap/pup procedures