



## AIR DRIVEN SAW

### Dimensions

Length(mm).....:	400	Width(mm).....:	41	Height(mm).....:	135
Equipment Weight - (kg).....:	3				
Lifting/ Transportation.....:	Transportation on pallet				

### Area of use / certification

Onshore/offshore.....:	Offshore
Standard.....:	Machinery Directive 2006/42/EC ATEX Directive 94/ 9/EC ATEX CE II 2G T5 X

### Type

Description.....:	Air driven saw - handheld
Fabricator.....:	Cengar
Model.....:	CL50
Serial no.....:	15109

### Flow / Pressure / Volume

Speed (stroke/min).....:	1200
Stroke length (mm).....:	45

### Connections

Air connection.....:	Please specify with order (Claw, hansen, osv)
Air supply (P@Q).....:	5-6 bar (max 6 bar) Air consumption : 0,168 m3/min

### Additional information

Equipment / Functions.....:	Must be used with water-separator and oil-lubricator.
-----------------------------	---

Blade must be ordered separately.  
 CL50: 12mm (1/2") wide Bi-Metal blad  
 Blade: TIGERSAGBLAD B624-5 (IKM item no:2053031)  
 Can be used with standard iron saw blade

- Vibration Level averaged 3,2 m/s<sup>2</sup>
- Sound Pressure Level 82.9 db.
- Sound Power Level 92.4 db.