



### DIAPHRAGM PUMP

#### Dimensions

Length(mm).....: 700                                      Width(mm).....: 600                                      Height(mm).....: 780  
Weight (kg).....: 92  
Lifting/ Transportation.....: Mounted in Frame. Transportation on pallet

#### Construction year

Built.....: 2019

#### Area of use / certification

Onshore/offshore.....: Offshore  
Standard.....: EX / Atex, CE, Norsok, Zone 1

#### Type

Fabricator.....: DEPA  
Model.....: DH80-FA-ZTT (3" pump house)  
Serial no.....: 781763-1

#### Technical information

Q-max (l/min).....: 700  
P-max (bar).....: 7                                      P-max (PSI).....: 100  
Max temp. (GrC).....: 130

#### Connections

Inlet connection.....: 2" Camlock Male  
Outlet connection.....: 2" Camlock Female  
Air connection.....: 1" offshore claw coupling  
Air supply (P@Q).....: Max 7 bar

#### Additional information

Equipment / Functions.....: Max suction, dry : 6,0 metres  
Max. solid size (mm) 25,0  
Minimum start pressure air : 1,5 Bar  
  
Pressure regulator on air supply to regulate flow / pressure.  
Bonding cable with clamp and documentation tube.  
Pump house material in aluminum.  
Enter medium, due to choice of gaskets.  
Frame and wet parts 316SS  
Frame and wet parts in acid-resistant material