



DIAPHRAGM PUMP

Dimensions

Length(mm).....	455	Width(mm).....	360	Height(mm).....	440
Weight (kg).....	18				
Lifting/ Transportation.....	Mounted in Frame. Transportation on pallet				

Area of use / certification

Onshore/offshore.....: Offshore
 Standard.....: EX/Atex, CE, Norsok, Zone 1

Type

Fabricator.....: RAASM
 Model.....: AAB-1-N-17069-9
 Serial no.....: 030700054-2022 (Art no. 3C3/26111 NHH)

Technical information

Q-max (l/min).....	170	P-max (PSI).....	115
P-max (bar).....	8		
Flowrate1.....	175 ltr/min @ 4 bar		
Flowrate2.....	155 ltr/min @ 6 bar		
Flowrate3.....	140 ltr/min @ 8 bar		
Max temp. (GrC).....	100		

Connections

Inlet connection.....: 1" Camlock Male
 Outlet connection.....: 1" Camlock Female
 Air connection.....: 1" offshore claw coupling
 Air supply (P@Q).....: Max 6,7 bar

Additional information

Equipment / Functions.....: Max suction, dry : 5,0 metres

Pressure regulator on air supply for flow / pressure control.
 Ground cable with clamp and documentation tube.
 Aluminum pump housing