



## NITROGEN TANK 20 BAR

### Dimensions

Length(mm).....: 2990                      Width(mm).....: 2437                      Height(mm).....: 2591  
Weight - Tara (kg).....: 6000                      Weight - Payload (kg).....: 7820                      Weight - Gross (kg).....: 13820  
Lifting/ Transportation.....: Frame with forklift channels and lifting slings are certified in acc. to DNV 2.7.1.  
Certificate(s) / Serial No:.....: AB1291 (Serial No. frame NT-167)

### Construction year

Built.....: 2019

### Area of use / certification

Onshore/offshore.....: Offshore

### Flow / Pressure / Volume

Tank Volume (ltr).....: 7376  
P-max (bar).....: 20  
P-max Transport (bar).....: 2  
Vaporization.....: Approx. 0,5% of total volume/day

### Connections

Inlet connection.....: ACME NI 150  
Outlet connection.....: ACME NI 150

### Filter

Inlet Filter house.....: Washable strainer

### Additional information

Equipment / Functions.....: TANK SHALL NOT BE FILLED MORE THAN 95% (7007 ltr)

Double set of safety valves, transport valve, drip pan under valve armatures, manometer and level gauge, lugs for tiedown.

To avoid condensation/icing, the tank must always be pressurised.